

<b>Snage jednostepenog reduktora zavisno od veličine reduktora, prenosnog odnosa i ulaznog broja obrtaja</b>											
u	n1	1	2	3	4	5	6	7	8	9	10
1.6	700	4	8	16	31.5	63	90	125	180	250	355
	950	5	10	20	40	80	112	160	224	315	450
	1400	6.3	12.5	25	50	100	140	200	280	400	560
2	700	3.2	6.3	12.5	25	50	71	100	140	200	280
	950	4	8	16	31.5	63	90	125	180	250	355
	1400	5	10	20	40	80	112	160	224	315	450
2.5	700	2.5	5	10	20	40	56	80	112	160	224
	950	3.2	6.3	12.5	25	50	71	100	140	200	280
	1400	4	8	16	31.5	63	90	125	180	250	355
3.15	700	2	4	8	16	31.5	45	63	90	125	180
	950	2.5	5	10	20	40	56	80	112	160	224
	1400	3.2	6.3	12.5	25	50	71	100	140	200	280
4	700	1.6	3.2	6.3	12.5	25	35.5	50	71	100	140
	950	2	4	8	16	31.5	45	63	90	125	180
	1400	2.5	5	10	20	40	56	80	112	160	224
5	700	1.25	2.5	5	10	20	28	40	56	80	112
	950	1.6	3.2	6.3	12.5	25	35.5	50	71	100	140
	1400	2	4	8	16	31.5	45	63	90	125	180
6.3	700	1	2	4	8	16	22.4	31.5	45	63	90
	950	1.25	2.5	5	10	20	28	40	56	80	112
	1400	1.6	3.2	6.3	12.5	25	35.5	50	71	100	140
8	700	0.8	1.6	3.2	6.3	12.5	18	25	35.5	50	71
	950	1	2	4	8	16	22.4	31.5	45	63	90
	1400	1.25	2.5	5	10	20	28	40	56	80	112
<b>Dimenzija</b>		<b>Osnovne mere reduktora</b>									
A		80	100	125	160	200	224	250	280	315	355
B		150	190	236	300	375	425	475	530	600	670
H		170	212	265	335	425	475	530	600	670	750
L		250	315	400	500	630	710	800	900	1000	1120

<b>Snage jednostepenog reduktora zavisno od veličine reduktora, prenosnog odnosa i ulaznog broja obrtaja</b>											
u	n1	1	2	3	4	5	6	7	8	9	10
10	1000	1.6	2.24	3.15	4.5	6.3	9	12.5	18	25	35.5
	1500	2	2.8	4	5.6	8	11.2	16	22.4	31.5	45
12.5	1000	1.25	1.8	2.5	3.55	5	7.1	10	14	20	28
	1500	1.6	2.24	3.15	4.5	6.3	9	12.5	18	25	35.5
16	1000	1	1.4	2	2.8	4	5.6	8	11.2	16	22.4
	1500	1.25	1.8	2.5	3.55	5	7.1	10	14	20	28
20	1000	0.8	1.12	1.6	2.24	3.15	4.5	6.3	9	12.5	18
	1500	1	1.4	2	2.8	4	5.6	8	11.2	16	22.4
25	1000	0.63	0.9	1.25	1.8	2.5	3.55	5	7.1	10	14
	1500	0.8	1.12	1.6	2.24	3.15	4.5	6.3	9	12.5	18
31.5	1000	0.5	0.71	1	1.4	2	2.8	4	5.6	8	11.2
	1500	0.63	0.9	1.25	1.8	2.5	3.55	5	7.1	10	14
40	1000	0.4	0.56	0.8	1.12	1.6	2.24	3.15	4.5	6.3	9
	1500	0.5	0.71	1	1.4	2	2.8	4	5.6	8	11.2
50	1000	0.32	0.45	0.63	0.9	1.25	1.8	2.5	3.55	5	7.1
	1500	0.4	0.56	0.8	1.12	1.6	2.24	3.15	4.5	6.3	9
60	1000	0.25	0.355	0.5	0.71	1	1.4	2	2.8	4	5.6
	1500	0.32	0.45	0.63	0.9	1.25	1.8	2.5	3.55	5	7.1
80	1000	0.2	0.28	0.4	0.56	0.8	1.12	1.6	2.24	3.15	4.5
	1500	0.25	0.355	0.5	0.71	1	1.4	2	2.8	4	5.6
	<b>Dimenzija</b>	<b>Osnovne mere reduktora</b>									
	A	71	80	90	100	112	125	140	160	180	200
	B	132	150	170	190	212	236	265	300	335	375
	H	236	265	300	335	375	425	475	530	600	670
	L	190	212	236	265	300	335	375	425	475	530